

MODEL TC-2000 OIL FREE VACUUM PUMP

SPECIFICATIONS

TYPE DUAL HEAD DRY PISTON PUMP
MAX VACUUM -97kPa WITH HEADS IN SERIES (TC-2000VS)
-85kPa WITH HEADS IN PARALLEL (TC-2000VP)

SERIES

VACUUM mmHg	0	100	200	300	400	500	600
AIR FLOW LPM	19	16	13	11	10	7	4

PARALLEL

VACUUM mmHg	0	100	200	300	400	500	600
AIR FLOW LPM	33	30	28	24	20	15	7

MOTOR SIZE 145 WATTS
ABSORBED POWER 90 WATTS
MOTOR VOLTAGE 220 – 240 V 50Hz

LENGTH 215mm
WIDTH 170mm AT HOSE BARB
HEIGHT 170mm – HANDLE FOLDED DOWN
WEIGHT 5 kg

CONSTRUCTION ALLOY HEADS, PLASTIC VALVE PLATE,
316 S/STEEL VALVES,
MOULDED SILICON RUBBER GASKETS AND
TEFLON SEALING RING

NOISE LEVEL **50 dB(A)** @ 1m

FEATURES

POWER CORD
ON/OFF SWITCH
FILTER/LIQUID TRAP/REGULATOR
DUAL SCALE VACUUM GAUGE
8MM HOSE BARB CONNECTOR
FOLDABLE CARRY HANDLE
NON SLIP RUBBER FEET

